

Bevel Cutters



For V- and J-seam profiles.

Bevel Cutters (V-seam)

Article	Beveling angle	Height of bevel max.		Bevel cutter-Ø		Code
	[°]	[mm]	[inch]	[mm]	[inch]	
Economy	30.0	9.5	.374"	72	2.835"	790 042 045
Economy	35.0	8.9	.350"	70	2.756"	790 042 037
Economy	37.5	8.4	.331"	70	2.756"	790 042 036
Economy	45.0	7.5	.295"	70	2.756"	790 042 038
Economy	60.0	4.7	.185"	70	2.756"	790 042 046
Performance	30.0	9.5	.374"	72	2.835"	790 042 071
Performance	30.0	13.0	.512"	76	2.992"	790 043 023
Performance	37.5	8.4	.331"	70	2.756"	790 042 070
Performance	50.0	5.8	.228"	70	2.756"	790 042 050
High-Performance	30.0	9.5	.374"	72	2.835"	790 042 073
High-Performance	37.5	8.4	.331"	70	2.756"	790 042 072

Bevel Cutters (J-seam)

Artikel	Beveling angle	Height of bevel		Bevel cutter-Ø		Code
	[°]	[mm]	[inch]	[mm]	[inch]	
Performance	15.0	9.0	.354"	67	2.638"	790 042 091
Performance	37.5	6.0	.236"	62	2.440"	790 041 042

High-Performance lubricants from Georg Fischer for cutting and beveling:
To increase the service life of your saw blades and bevel cutters



GF TOP

The lubrication is a synthetic high-performance lubricant for cutting and beveling. It complies with USDA H2 registration. Regulated application by a brush. 180 g

Code 790 060 228



ROCOL

Oil-based high-performance lubricant.

150 ml

Code 790 041 016

The technical data are not binding. They are not warranted and characteristics are subject to change. Please consult our general conditions of supply.

GF Piping Systems → Sales & Service worldwide

USA

Georg Fischer Inc., 2882 Dow Avenue, Tustin, CA 92780-7258, Tel.+1(714)731-88 00, Toll Free 800/854 40 90, Fax +1(714)731 62 01, us.ps@georgfischer.com, www.us.piping.georgfischer.com

D/Export

Georg Fischer Rohrverbindungstechnik GmbH, Freibühlstrasse 18/19, 78224 Singen (Htwl.), Germany, Phone +49 (0) 77 31 / 792 787 up to 789, Fax +49 (0) 77 31 / 792 524, rvt.ps@georgfischer.com, www.rvt.georgfischer.com

